

# Product Options



14.5mm (2.5mm+12mm) x 48" (1.2m)



14.5mm (2.5mm+12mm) x 23" (58cm) x 23" (58cm)

## Physical Data

PERFORMANCE CRITERIA	TEST	RESULT
Tensile Strength	ASTM D 412	>200 PSI
Flexibility ¼" mandrel	ASTM F 137	Pass
Thermal Conductivity	ASTM C 518	>0.4
Static Load Limit	ASTM F 970 @ 250PSI	0.009" Typical
Coefficient of Friction	ASTM D 2047	> 0.9
V.O.C. Compliant	ASTM D 5116	Yes
Abrasion Resistance	ASTM D 3389 / EN 649	<1g, 100 cycles
Pill Test	ASTM D 2859	Pass
Vertical Deflection / Deformation	ASTM F 2772	2.66mm
Surface Effect Slip Resistance	ASTM F 2772	Pass
Ball Rebound	ASTM F 2772	98.8%
Force Reduction	ASTM F 2772	35.7%

Can a track lessen the amount of forceful impact on your body, and keep you running longer with less joint pain?



Yes.

### Stacked Performance Rally

is a 14.5mm surface tailored for heavy conditioning and is available in both rolls and interlocking tiles.

ecore | Built by Yes.



## What does it take to be a floor?

- Durable
- Sustainable
- Affordable
- Ease of Maintenance
- Slip Resistant

With a durable wear layer made from vulcanized EPDM rubber, this product resists the scuffing and marking that is common in strength and conditioning applications.




## Can a floor do more? Yes.

This 14.5mm product showcases a dynamic force reduction of 35.40%. This dual durometer system is engineered to absorb the impact force related to aggressive functional training, providing an ergonomically advanced surface that works in concert with the body.


### Applications



Cardio



Light Weights



Moderate Weights



Extreme Functional Training



Tracks



Strength Equipment



Functional Training

